## **CLAIM AMENDMENTS**

- 1. (Amended) A filtration media for drinking water which is composed of comprising 5% to 15½ zirconia particles, 60% to 80% activated carbon particles, and 15½ to 25½ of an organic binder material binding together the zirconia and activated carbon particles into a rigid porous solid, all percentages by weight based on the total composition.
- 2. (Amended) A filtration media in accordance with Claim 1, wherein the carbon content is about 70% by weight, based on the total composition.
- 3. (Amended) A filtration media in accordance with Claim 1, which in composed of about 10% zirconia, about 70% activated carbon, and the balance of binder material, all percentages by weight based on the total composition.
- 4. (Amended) A filtration media for a small filter wherein the media occupies a space less than about 20 cubic inches and wherein the filtration media is composed of 15% to 25% zirconia particles, 45% to 60%, activated carbon particles, and the balance of an organic binder material binding together the zirconia and activated carbon particles into a rigid porous solid, all percentages by weight based on the total composition.
- 5. (Amended) A filtration media in accordance with Claim 4, wherein the zirconia content is about 20% by weight based on the total composition.

- 6. (Amended) A filtration media in accordance with Claim 4, wherein the zirconia content is about 25%t and the carbon content is about 60%, each by weight based on the total composition.
- 7. (Withdrawn) A filtration media for the filtration of drinking water which is composed of: amorphous aluminosilicate material wherein the major portion of its pores have diameters in the range of 60 Angstroms to 100 Angstroms, 5% to 10%: activated carbon, 60% to 70%: zirconia, 53 to 15%: and a binder of at least 15%.
- 8. (Withdrawn) A filtration media in accordance with Claim 7, wherein the aluminosilicate content is about 10%, and the activated carbon content is about 65%.
- 9. (Withdrawn) A filtration media in accordance with Claim 7, wherein the zirconia content is about lot.
- 10. (Amended) A filtration media for drinking water, comprising which is composed of zirconia of about 4% to 15% by weight zirconia particles, activated carbon of about 65% by weight activated carbon particles, alumina of about 5% to 15% by weight alumina particles, and a balance of at least lot 10% by weight of binder material binding together the zirconia, alumina, and activated carbon particles into a rigid porous solid, each based on the total composition.

- 11. (Amended) A filtration media in accordance with claim 10, wherein the content of said zirconia is about 10% by weight, based on the total composition.
- 12. (Amended) A filtration media in accordance with Claim 10, wherein said alumina content is about lot 10% by weight, based on the total composition.
- 13. (Withdrawn) A filtration media for drinking water which is composed of silica gel (60 Angstroms) of about 5% to 10%, activated carbon of about 70% to 80%, and binder material of a minimum of about 15%.
- 14. (Withdrawn) A filtration media in accordance with Claim 13, wherein the content of said silica gel (60 Angstroms) is about 10% and the content of said activated carbon is about 75%.
- 15. (Withdrawn) A filtration media for drinking water which is composed of silica gel (60 Angstroms) of about 5% to 10%, zirconia of about 5% to 15%, activated carbon of about 60% to 70%, and binder material of not less than about 10%.
- 16. (Withdrawn) A filtration material in accordance with Claim 15, wherein the content of said zirconia is about 10%.
- 17. (Withdrawn) A filtration media in accordance with Claim 15, wherein the content of said activated carbon is about 65%.

- 18. (Withdrawn) A filtration media for drinking water which is composed of silica gal (60 Angstroms) 50% to 70%, zirconia of about 15% to 25%, and binder material of about 15% to 25%.
- 19. (Withdrawn) A filter material in accordance with Claim 18, wherein the content of said silica gal (60 Angstroms) is about 60%.
- 20. (Withdrawn) A filtration media in accordance with Claim 18, wherein the content of said zirconia is about 15%.
- 21. (Withdrawn) A filtration media in accordance with claim 18, wherein the content of said silica gel (60 Angstroms) is about 60%.
- 22. (Withdrawn) A filtration media for drinking water which is composed of aluminosilicate of about 5% to 15%, zirconia of about 5% to 15%, silica gal (60 Angstroms) or about 5% to 10%, activated carbon of about 50% to 70% and binder material of 15% to 25%.
- 23. (Withdrawn) A filtration media in accordance with Claim 22, wherein said activated carbon content is about 60%.

- 24. (Withdrawn) A filtration media in accordance with Claim 22, wherein said zirconia content is about 5%.
- 25. (Withdrawn) The use of zirconia as a filtration media to remove fluorides from drinking water.
- 26. (Withdrawn) A water filter composed of zirconia which has been molded into a desired shape from zirconia powder mixed with 10% to 30% binder material.
- 27. (Withdrawn) A method of regenerating a filtration media composed of zirconia which comprises flowing a 5% sodium hydroxide fluid through it for a sufficient period of time for the removal of ions from the filtration media.
- 28. (Withdrawn) A filtration media for drinking water at point-of-use which comprises in series alumina filtration media and zirconia filtration media, of respective percentage ratios of between about 4 to 1 and 1 to 1.
- 29. (Withdrawn) A filter for use in filtering drinking water at point-of-use which comprises, in series, first a filtration media composed of alumina, and second a filtration media composed of zirconia.
- 30. (Withdrawn) The use of zirconia as a filtration media to remove arsenic from drinking water.

- 31. (Withdrawn) A filtration media for the removal of heavy metals and organic substances in drinking water which is composed of silica gel (60 Angstroms), aluminosilicate and activated carbon.
- 32. (Withdrawn) A filtration media to reduce chloroform and VOC from drinking water which comprises a mixture of silica gel (60 Angstroms) and carbon block which was made from coconut shell.
- 33. (Withdrawn) A filtration media which is composed of about 7% zirconia, 7% silica gel (60 Angstroms), 7% aluminosilicate and about 79% activated carbon.
- 34. (Withdrawn) A filtration media which is composed of about 20% silica gel (60 Angstroms) and about 80% activated carbon.
- 35. (Withdrawn) A filtration media which is composed of about 15% silica gel (60 Angstroms), about 15% aluminosilicate and about 70% activated carbon.
- 36. (Withdrawn) A filtration media which is composed of about 70% activated carbon, about 10% aluminosilicate, about 10% zirconia and about 10% silica gel (60 Angstroms), said activated carbon being coated with said aluminosilicate, zirconia and silica gel (60 Angstroms).

- 37. (Withdrawn) A filtration media which is contained in volumes from 5 cubic inches to 3,000 cubic inches and which is composed of a mixture of zirconia, silica gel (60 Angstroms) and carbon block.
- 38. (Withdrawn) A filtration media which is composed of a mixture of silica gel (60 Angstroms) and activated carbon, wherein said silica gel (60 Angstroms) is coated on granulars of said activated carbon.
- 39. (Withdrawn) A filtration media for removing arsenic, chloroform and fluorides from drinking water which is composed of zirconia in granular form.
- 40. (Withdrawn) A filtration apparatus comprising a gravity column having a first stage which contains a filtration media composed of alumina (gamma, acid washed) and a second stage containing a filtration media composed of zirconia.
- 41. (Withdrawn) A filtration media comprising a mixture of zirconia and granular or powdered activated carbon.